

# KPC132



## DOME CAMERA

### ● OVERVIEW

Equipped with a 1/3" Color CCD image sensor, this mini dome camera possesses satisfactory minimum illumination to provide clear and sharp images. It can be easily installed at any places for users to monitor a wider area.

### ● FEATURES

- (1) 420 TV lines of horizontal resolution and high quality picture
- (2) 1/3" color CCD sensor
- (3) Minimum Illumination 0.4 Lux / F2.0
- (4) S/N Ratio is more than 48dB (AGC off)
- (5) High reliability under long time operation

### ● SPECIFICATIONS\*

Model	KPC132
Pick up Element	1/3" Color CCD image sensor
Number of Pixel	512(H) x 492(V) <NTSC> / 512(H) x 582(V) <PAL>
Resolution	420 TV lines
Min. Illumination	0.4 Lux / F2.0
S/N Ratio	More than 48dB (AGC off)
Electronic Shutter	1/60 (1/50) to 1/100,000 sec.
Lens Mount	C/CS mount changeable
Lens	f3.6mm / F2.0
Lens Angle	92.6°
Iris Mode	AES
AGC	Auto
White Balance	ATW
Video Output	1.0Vp-p composite, 75Ω
Power Source (10%)	DC12V
Current Consumption (10%)	110mA
Dimension (mm)**	100(Ø) × 60(H)
Gross Weight (g)	203.5

\* The specifications are subject to change without notice.

\* Dimensional Tolerance: ± 5mm